

Infratouch Touchscreen Keypad

Product Overview

The Infratouch Touchscreen Keypad features a digital, multi-color display with simple touchscreen functions used to arm and disarm security as well as show system options and identify problems.

Infratouch also features a top mounted, status indicating LED light useful for notifying personnel of the keypad's arming states at a distance.

The Infraguard II intrusion detection system can support up to 16 keypads per panel using ASN6 and 8 keypads



Expertise you can rely on.

DIMENSIONS

Size

- 3.12" L x 5.42" W x 1.27" D

Weight

- 6.4oz

HOUSING

- Plastic, Off-white

OPERATING ENVIRONMENT

- 14° F to 122° F (-10° C to 50° C)
- Humidity Non-condensing
- Indoor use

POWER REQUIREMENTS

- Input voltage: 7V-14.0VDC
- 171mA avg, 310mA max @ 13.7V

DISPLAY

- Touchscreen Display
- 480 x 272 24 Bit Color LCD
- Multi-Color Status LED

COMMUNICATIONS

- RS485 (up to 2000')

MOUNTING

- 4 - #8 Screws
- Mounting Box

WIRING

- Minimum 22AWG 2-Pair Twisted with OA Shield
 - o Requires ASN5 sp6, panel firmware V7.101 or higher, or ASN V6

PART NUMBERS

INFRATOUCH Infratouch Touchscreen Keypad

07917203 Back Mounting Box

INSTALL-GD0102 Infratouch Touchscreen Keypad Installation Guide

USER-GUIDE-0103 Infratouch Touchscreen Keypad User's Guide

